



S型
"S"Type

R型
"R"Type

F型
"F"Type

链号 Chain No.	节距 Pitch					内节 内宽 Inside width	链板 高度 Plate depth	销轴 直径 Pin dia.	套筒 直径 Barrel dia.	链板 厚度 Plate thickness	滚子尺寸 Roller dimension				销轴 长度 Pin length		抗拉强度 Ultimate tensile strength
											d4	d1	d5	d6	L	Lc	Q
	P					b1	h2	d2	d3	T	d4	d1	d5	d6	L	Lc	Q
	mm					mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	KN
FV40	40	50	63	80	100	18	26	10	15	3	20	32	40	48	37	39.5	40
FV63	63	80	100	125	160	22	30	12	18	4	26	40	50	60	46	50.5	63
FV90	63	100	125	160	200	25	35	14	20	5	30	48	63	73	53	57.5	90
FV112	100	125	160	200	250	30	40	16	22	6	32	55	72	87	63	67.5	112
FV140	100	125	160	200	250	35	45	18	26	6	36	60	80	95	68	74.0	140
FV180	125	160	200	250	315	45	50	20	30	8	42	70	100	120	86	93.0	180
FV250	160	200	250	315	400	55	60	26	36	8	50	80	125	145	98	106.0	250
FV315	160	200	250	315	400	65	70	30	42	10	60	90	140	170	117	125.0	315
FV400	160	200	250	315	400	70	70	32	44	12	60	100	150	185	131	141.0	400
FV500	200	250	315	400	500	80	80	36	50	12	70	110	160	195	141	151.0	500
FV630	200	250	315	400	500	90	100	42	56	12	80	120	170	210	153	163.0	630