



ANSI 链号 ANSI Chain No.	节距 Pitch P mm	滚子直径 Diameter of Roller d1(max) mm	销轴直径 Diameter of Pin d2 mm	销轴长度 Length of Pin L(max) mm	内节内宽 Inner Width of Inner Link b1(min) mm	内链板高度 Height of Inner Sidebar h2 mm	抗拉强度 Tensile Strength Q(min) KN	每米重量 Weight per Meter q kg/m
C2040SS C2042SS	25.40	7.95 15.88	3.96	17.80	7.85	12.70	8.2	0.50 0.84
C2050SS C2052SS	31.75	10.16 19.05	5.08	21.00	9.40	15.09	15.6	0.78 1.27
C2060HSS C2062HSS	38.10	11.91 22.23	5.94	29.90	12.57	18.08	19.7	1.44 2.07
C2080SS C2082SS	50.80	15.88 28.58	7.92	33.50	15.75	24.13	35.8	2.08 3.12
C2100SS C2102SS	63.50	19.05 39.67	9.53	41.40	18.90	30.18	54.5	3.01 4.83
C2100HSS C2102HSS	63.50	19.05 39.67	9.53	44.10	18.90	30.18	54.5	3.60 5.38
C2120SS C2122SS	76.20	22.23 44.45	11.10	50.40	25.22	36.10	79.2	4.66 7.66
C2120HSS C2122HSS	76.20	22.23 44.45	11.10	53.50	25.22	36.10	79.2	5.26 8.26