



链号 China No.	节距 Pitch P mm	内链节内宽 Inner Width of Inner Link $b_1(\max)$ mm	滚子直径 Diameter of Roller $d_1(\max)$ mm	链板高度 Height of Sidebar $h_2(\max)$ mm	链板厚度 Thickness of Sidebar T mm	销轴长度 Length of Pin L max	销轴直径 Diameter of Pin $d_2(\max)$ mm	抗拉强度 Tensile Strength Q(min) KN	每米重量 Weight per Meter q kg/m
2010	63.50	38.10	31.75	47.80	7.90	90.70	15.90	262.00	14.0
2510	78.1	31.75	36.9	40	8.0	94.8	16.00	271.00	10.7
2512	77.90	39.60	41.28	57.00	9.70	103.40	19.08	378.00	18.0
2814	88.90	38.10	44.40	60.50	12.70	117.60	22.25	516.00	25.0
3315	103.45	49.30	45.24	63.50	14.20	134.60	23.85	596.00	27.0
3618	114.30	52.30	57.15	79.20	14.20	141.20	27.97	814.00	38.0
4020	127.00	69.90	63.50	91.90	15.70	168.10	31.78	1054.00	52.0
4824	152.40	76.20	76.20	104.6	19.00	187.50	38.13	1521.00	68.0
WG /WB系列参数 WG/WB Serial Data									
WG781	78.18	38.1	33.0	45.0	10.0	97.0	17.00	313.60	16.0
WG103	103.20	49.2	46.0	60.0	13.0	125.5	23.00	539.00	26.0
WG140	140.00	80.0	65.0	90.0	20.0	187.0	35.00	1176.00	59.2
WB9525	95.25	39.0	45.0	65.0	16.0	124.0	23.00	635.00	22.2
WB7900	79.00	39.0	31.5	54.0	9.5	93.5	18.50	381.00	12.8
WB7938	79.38	41.2	40.0	57.2	9.5	100.0	19.50	509.00	18.7
WB238	88.9	36.8	44.40	57.2	12.7	113.4	22.15	501.4	25.4
WB1207	127.0	68.3	63.50	88.9	15.7	158.3	31.75	1044.0	53.1