

链号 Chain No.	节距 Pitch P mm	滚子直径 Diameter of Roller d ₁ (max) mm	销轴直径 Diameter of Pin d ₂ mm	销轴长度 Length of Pin b ₂ mm	内节内宽 Inner Width of Inner Link b ₁ (min) mm	链板厚度 Thickness of Sidebar T mm	链板高度 Height of Sidebar h ₁ mm	附板高度 Height of Attached Sidebar h ₂ mm	抗拉强度 Tensile Strength Q(min) KN
Ne机型提升链 Lifting Chain for Ne Model Machine									
NE15-101.6	101.60	26.5	11.50	70	27.0	6	35	35.0	128.1
NE30-152.4	152.40	35.0	15.50	90	36.5	8	50	50.0	245.0
NE50-152.4	152.40	35.0	15.50	90	36.5	8	50	110.0	245.0
NE100-200	200.00	42.0	19.10	120	51.8	10	60	125.0	375.0
NE150-200	200.00	48.5	22.23	120	57.8	10	60	125.0	375.0
NE300-250	250.00	70	35	165	75	16	100	150.0	450.0
NE300-250	250.00	63.5	31.75	146	67.4	12	90	150.0	450.0
NP152.4	152.40	357	15.88	88	38	7.9	45	105	245.0
FE12600	152.40	35	15.88	86	36.5	7.9	45	120	245.0

附件尺寸 Dimensions of Attachment

链号 Chain No.	d ₄	L ₁	L ₂
NE15-101.6	10	50	50
NE30-152.4	15	75	70
NE50-152.4	15	75	70
EF100-200	15	75	70
EF150-200	18	100	80
NE300-250	18	140	100
NE300-250A	20	140	100
NP152.4	15	75	70
FE12600	15	75	70