



过渡连接链节

Transitional Connecting Chain Link

链号 China No.	节距 Pitch  P mm	内节内宽 Inner Width of Inner Link  b <sub>1</sub> mm	滚子直径 Diameter of Roller  d <sub>1</sub> (max) mm	耳形附件参数 Data of Ear-Shaped Attachment						销轴参数 Data of Pin			抗拉强度 Tensile Strength  Q(min) KN
				A mm	C mm	X mm	N mm	d <sub>4</sub> mm	T mm	d <sub>2</sub> mm	L <sub>1</sub> mm	L <sub>2</sub> mm	
SMKW0909	93.70	27.6	44.5	46.8	44.0	59.0	31.8	16.3	13.5	15.9	33.0	40.0	95
SMKW1010	101.60	32.6	50.8	50.8	50.8	64.8	35.0	11.1	10.3	12.7	37.5	42.5	100
SMKW1510	101.60	32.6	50.8	50.8	54.0	75.0	42.0	16.3	12.7	17.5	39.0	45.0	155
SMKW1810	101.60	29.4	50.8	50.8	58.7	76.0	32.0	16.3	12.7	17.5	37.5	43.5	180
SMKW09102	102.60	37.5	50.8	50.8	60.3	80.3	49.5	16.3	13.5	17.5	38.0	45.0	95
SMKW15152	102.60	37.6	63.5	76.2	62.0	82.0	80.0	16.3	15.0	19.1	38.5	45.5	155
SMKW20152	152.40	34.9	76.2	76.2	66.7	92.0	50.0	16.3	16.0	22.23	45.0	54.0	200
SMKW34150	152.40	34.9	76.2	76.2	66.7	92.0	50.0	16.3	16.0	22.23	45.0	54.0	340
SMKW23152	152.40	36.5	69.9	76.2	66.7	90.0	40.0	16.3	16.0	19.1	44.5	52.0	235
SMKW31152	152.40	36.5	69.9	76.2	66.7	90.0	40.0	16.3	16.0	19.1	44.5	52.0	310
SMKW38152	152.40	36.5	69.9	76.2	66.7	90.0	40.0	16.3	16.0	19.1	44.5	52.0	385