



链号 chain NO.	节距 Pitch P mm	套筒外径 Diameter of Bushing d1(max) mm	销轴直径 Diameter of Pin d2 mm	链板高度 Height of Sidebar h2(max) mm	小端内宽 Inner Width of Close End b1(max) mm	小端外宽 Outer Width of Close End b2(max) mm	链板厚度 Thickness of Sidebar T(max) mm	抗拉强度 Tensile Strength Q(min) KN	每米重量 Weight per Meter q kg/m
WH78	66.27	22.23	12.70	28.4	28.4	51	6.4	150	5.9
DWR78	66.27	21.20	14.28	32.0	28.4	51	6.4	130	6.4
DWH78	66.27	21.20	14.28	32.0	28.4	51	6.4	170	6.4
WR78B	66.27	22.20	12.7	28.4	28.6	51	6.4	93.4	5.9
WR78H	66.95	25.4	14.27	32	25.4	51	9.5	127	12.7
WH78H	66.95	25.4	14.24	32	25.4	51	9.5	158	12.7
WH78C	66.27	22.5	12.7	28.4	28.6	52.3	7	180	7.1
WR78SS	66.27	21.2	12.7	28.4	28	52.3	7	85	7.1
WR82	78.10	27	14.29	32	44	57	6.4	93.4	5.8
WH82R	78.10	25.4	14.29	32	44	57	6.4	150	5.75
WH82X	78.10	31.78	19.05	38.1	50.15	60.3	9.5	169	15.6

注:WR78SS材质为:Cr13, WH78C链板材质为:35CrMo

Note: the material of WR78SS is Cr13 and the material of chain plate WH78C is 35CrMo