



链号 Chain No.		节距 Pitch	滚子外径 Roller dia.	内链节内宽 Inside Width	销轴直径 Pin dia.	内链板高度 Height of inner plate	排距 Transverse pitch	抗拉强度 Ultimate tensile strength	重量 Weight approx.
ANSI	ISO	P mm	d1(max) mm	b1(min) mm	d2(max) mm	h2 mm	Pt mm	Q KN	q kg/m
25-1							-	3.50	0.15
25-2	04C	6.35	3.30*	3.10	2.31	6.02	6.40	7.00	0.28
25-3								10.50	0.41
35-1							-	7.90	0.35
35-2	06C	9.525	5.08*	4.68	3.60	9.05	10.13	15.80	0.69
35-3								23.70	1.02
41-1							-	6.70	0.41
41-2	085	12.70	7.77	6.25	3.60	9.91	11.95	13.30	0.80
40-1							-	13.90	0.66
40-2	08A	12.70	7.92	7.85	3.98	12.07	14.38	27.80	1.30
40-3								41.70	1.96
50-1							-	21.80	1.10
50-2	10A	15.875	10.16	9.40	5.09	15.09	18.11	43.60	2.14
50-3								65.40	3.20
60-1							-	31.30	1.53
60-2	12A	19.05	11.91	12.57	5.96	18.10	22.78	62.60	3.00
60-3								93.90	4.50
80-1							-	55.60	2.63
80-2	16A	25.40	15.88	15.75	7.94	24.13	29.29	111.20	5.24
80-3								166.80	7.83
100-1							-	87.00	4.03
100-2	20A	31.75	19.05	18.90	9.54	30.17	35.76	174.00	8.02
100-3								261.00	12.00