



ISO 链号 Chain No.	节距 Pitch	滚子外径 Roller dia.	内节内宽 Inside Width	销轴直径 Pin dia.	链板厚度 Plate thickness	链板高度 Plate depth	排距 Transverse pitch	销轴长度 Pin Length	抗拉强度 Ultimate tensile strength	重量 Weight approx.
ISO	P	d1(max)	b1(min)	d2(max)	T	h2	Pt	L	Q	q
	mm	mm	mm	mm	mm	mm	mm	mm	KN	kg/m
C08B-1							-	17.00	17.8	0.8
C08B-2	2.7	8.51	7.75	4.45	1.60	11.81		31.00	31.1	1.58
C08B-3							13.92	44.90	44.5	2.36
C10B-1							-	19.60	22.2	1.01
C10B-2	15.875	10.16	9.65	5.08	1.70	14.73		36.20	44.5	2
C10B-3							16.59	52.80	66.7	2.99
C12B-1							-	22.70	28.9	1.31
C12B-2	19.05	12.07	11.68	5.72	1.85	16.13		42.20	57.8	2.6
C12B-3							19.46	61.70	86.7	3.89
C16B-1							-	36.10	60	2.97
C16B-2	25.40	15.88	17.02	8.28	4.0/3.0	21.08		68.00	106	5.89
C16B-3							31.88	99.90	160	8.81
C20B-1							-	43.20	95	4.12
C20B-2	31.75	19.05	19.56	10.19	4.5/3.5	26.42		79.70	170	8.16
C20B-3							36.45	116.10	250	12.2
C24B-1							-	53.40	160	7.52
C24B-2	38.10	25.40	25.40	14.63	6.0/4.8	33.40		101.80	280	14.87
C24B-3							48.36	150.20	425	22.22
C28B-1							-	65.10	200	9.87
C28B-2	44.45	27.94	30.99	15.9	7.5/6.0	37.05		124.70	360	19.54
C28B-3							59.56	184.30	530	29.21
C32B-1							-	67.40	250	10.53
C32B-2	50.80	29.21	30.99	17.81	7.0/6.35	42.29		126.00	450	20.78
C32B-3							58.55	184.50	670	31.03

传动链 TRANSMISSION CHAIN