



链号 China No.	节距 Pitch P mm	滚子直径 Diameter of Roller d ₁ (max) mm	内节内宽 Inner Width of Inner Link b ₁ (min) mm	销轴直径 Diameter of Pin		销轴长度 Length of Pin L(max) mm	内链板高度 Height of Inner Sidebar h ₂ (max) mm	抗拉强度 Tensile Strength Q(min) KN	每米 Weight Mer q kg/
				d ₂ (max) mm	d ₃ (min) mm				
				C2052HP	31.75				
C2062HP	38.10	22.23	12.70	8.31	6.00	25.8	17.00	24.0	1.7
63HPEI	63.00	40.00	15.00	16.00	12.10	35.0	28.350	50.0	4.2
HP50	50.00	31.00	14.50	13.20	10.43	31.1	25.00	30.0	3.2
FK8404HP	101.60	47.60	19.00	19.05	13.60	43.8	39.00	84.3	5.7
FK1650HP	50.80	30.00	10.50	11.40	8.2	27.4	26.00	50.0	2.5
6DC28HP	152.4	66.7	38.0	26.92	19.56	94.3	50.8	266.6	27.0
4DC15H	101.6	47.6	19.1	19.05	13.2	47	38.1	66.7	6.3
HC060030	76.2	31.8	15.0	14.0	10.1	39	25.5	27.0	3.1
HC060040	101.6	31.8	15.0	14.0	10.1	39	25.5	27.0	2.8
HC120040	101.6	47.6	19.05	19.05	13.2	47	38.1	54.0	5.8
HC060060	152.4	31.8	15.0	14.0	10.1	39	25.5	27.0	2.5
HC360060	152.4	88.9	38.1	31.8	22.9	83	61	160.0	29.0
HB10C63	63.0	30	10.0	11.5	8.2	26.6	26	35.0	4.0