



## Single-Style B and C-Steel-Instant Split-Sprocket

Hub Number	Bore:d	Hub Dh	Hub* Length	Bolts	Wt. (Lbs.)
S-1	3/4"-1 1/2"	3 1/8"	1"	3/8" X 2 1/4"	1.8
S-2	1 3/8"-2 1/4"	4 3/8"	1 1/4"	1/2" X 3"	4.1
S-3	1 1/2"-3"	6"	1 3/8"	5/8" X 4 1/2"	8.4
S-4	1 3/4"-4"	7 5/8"	1 1/2"	3/4" X 5 1/2"	14.4
S-5	1 3/4"-5"	9 1/4"	2"	1" X 6"	27.8
S-6	1 3/4"-6"	10 1/4"	2 1/4"	1" X 6"	35.4
S-7	1 3/4"-7"	12 1/2"	2 1/2"	1" X 7"	64.4
S-8	1 3/4"-8"	14 1/2"	3"	1" X 8"	98.5

Add hub length to plate thickness to determine length thru bore.

For style C and hub length X 2.

## Sprocket Size For Instant Split Hubs

Split Hub No	Num of Teeth (min)	Chain Num	Bore										
			40	50	60	80	100	120	140	160	180	200	240
S-1	3/4"-1 1/2"		28	23	20	16	-	-	-	-	-	-	-
S-2	1 3/8"-2 1/4"		38	30	26	20	17	15	14	-	-	-	-
S-3	2"-3"		46	37	32	25	20	18	16	15	14	-	-
S-4	2 3/4"-4"		-	48	40	30	25	21	19	17	16	15	12
S-5	3 3/4"-5"		-	-	-	-	30	25	22	20	18	17	14
S-6	4 3/4"-6"		-	-	-	-	32	27	24	22	19	18	15
S-7	5 3/4"-7"		-	-	-	-	-	32	28	25	22	21	18
S-8	6 1/4"-8"		-	-	-	-	-	-	-	28	25	23	20

\* Manufactured from stock plate sprockets. Instant Split-Sprocket Offers unlimited and is Simply installed with a hard wrench ... greatly reducing costly downtime.

\* Instant Split Hubs are for use with plate sprockets only. For multiple strand split sprockets consult factory.